

Declaration of Performance

Product Type Identification: **BETONYP®**

Type: **BETONYP® Cement-Bonded Chipboard (8-40 mm)**

Manufacturer: **FALCO Zrt., Zanati u. 26.,9700, Szombathely, Hungary**

Notified Body: **ÉMI (accredited Hungarian control institute for the building industry) Budapest - Head Office, addr: 1113 Budapest, Diószegi út 37.**

Importer: **CZECHCEMENTBOARD s.r.o., Opletalova 921/6, Prague 110 00, Czech Republic**

| Essential characteristics | Performance | Harmonized technical specification |
|--|----------------------------|------------------------------------|
| Fire class | B-s1, d0 | EN 13986:2004 |
| Durability (moisture resistance) | max. 1.5% | EN 13986:2004 |
| Bending strength | min. 9 N/mm ² | EN 13986:2004 |
| Vertical tensile strength to the board | min. 0.5 N/mm ² | EN 13986:2004 |
| Modulus of elasticity | 4500 N/mm ² | EN 13986:2004 |
| Swelling (after 24 hours of soaking) | max. 1.5% | EN 13986:2004 |

The product performance is consistent with the properties indicated in the table.

Prague 2019-01-05

CZECH CEMENT BOARD s.r.o.
Opletalova 921/6
110 00 Praha 1
IC: 05365724

Ing. Stanislav Beránek
Executive director of Importer